



SICMA[®] srl

HARVESTERS FOR OLIVES, NUTS AND HANGING FRUITS

SICMA

ANTIUSURA



TRINCIASARMENTI

CARATTERISTICHE TECNICHE

Trasmissione a 5 cinghie - Spostamento laterale idraulico
Attacco a tre punti 1° 2° cat. - Rullo Ø 220 mm, spessore lamiera da 8 mm
Scatola con dispositivo a ruota libera - Telaio rinforzato - Albero cardanico - PTO 540 - Serraggio martelli M22 Ø 20 mm - Lamelle spessore 10 mm
Cassa rinforzata ANTIUSURA da 10 mm di spessore

Modello		140	150	160	170	180	190	200	220	235
Ingombro	cm	158	168	178	188	198	208	218	238	253
Larghezza operativa	cm	140	150	160	170	180	190	200	220	235
Martelli	#	8	10	12	14	16	16	18	20	22
Spessore rotore	mm	14	14	14	14	14	14	14	14	14
Diametro rotore	mm	175	175	175	175	175	175	175	175	175
Spessore Rullo	mm	8	8	8	8	8	8	8	8	8
Diametro rullo	mm	220	220	220	220	220	220	220	220	220
Spessore Cassa	mm	10	10	10	10	10	10	10	10	10
Trasmissione		B 8	B 8	B 8	B 8	B 8	B 8	B 8	B 8	B 8
Potenza raccomandata	CV	40	50	50	55	60	65	70	80	90
Peso	Kg	627	652	676	700	725	750	775	823	860



Loc. Callipo, Z.I., 88022 Acconia di Curinga (CZ), Italy
Partita IVA/Vat # 01805340799

+39 0968 78240

www.sicmasrl.com

info@sicmasrl.com - international@sicmasrl.com





SICMA[®]
srl

HARVESTERS FOR OLIVES, NUTS AND HANGING FRUITS

SICMA



ANTI-WEAR
metal sheet

FLAIL MOWER/MULCHER

TECHNICAL SPECIFICATIONS

5-belt transmission - Hydraulic side shift - three-point linkage cat 1° - 2°
 Rear roller of Ø 220 mm with steel metal thickness of 8 mm - Freewheel box mechanism
 Cardan Power shaft - PTO 540 - M22 tightening with Ø 20 mm bolts
 Blades of 10 mm thick - Reinforced ANTI-WEAR metal box of 10 mm



Modello		140	150	160	170	180	190	200	220	235
Total width	cm	158	168	178	188	198	208	218	238	253
Working width	cm	140	150	160	170	180	190	200	220	235
Hammers	#	8	10	12	14	16	16	18	20	22
Rotor thickness	mm	14	14	14	14	14	14	14	14	14
Rotor Ø	mm	175	175	175	175	175	175	175	175	175
Rear roller thickness	mm	8	8	8	8	8	8	8	8	8
Rear roller Ø	mm	220	220	220	220	220	220	220	220	220
Main box thickness	mm	10	10	10	10	10	10	10	10	10
Transmission		B 8	B 8	B 8	B 8	B 8	B 8	B 8	B 8	B 8
Recommended power	CV	40	50	50	55	60	65	70	80	90
Weight	Kg	627	652	676	700	725	750	775	823	860

Loc. Callipo, Z.I., 88022 Acconia di Curinga (CZ), Italy
 Partita IVA/Vat # 01805340799

+39 0968 78240

www.sicmasrl.com

info@sicmasrl.com - international@sicmasrl.com

