



# SICMA<sup>®</sup> srl

Harvesters for Olives, Nuts and Hanging Fruits

## FLAIL MOWER/MULCHER



### **TECHNICAL CHARACTERISTICS**

5-belt transmission – Hydraulic side shift – three-point linkage cat 1° - 2° – Rear roller  $\varnothing$  220 mm - freewheel box mechanism – Reinforced chassis – Cardan Power shaft - PTO 540 – Reduced power requirement - Anti-wear Ardox sheet metal

<b>Type</b>		<b>140</b>	<b>150</b>	<b>160</b>	<b>170</b>	<b>180</b>	<b>190</b>	<b>200</b>	<b>220</b>	<b>235</b>
Max size	cm	158	168	178	188	198	208	218	238	253
Working width	cm	140	150	160	170	180	190	200	220	235
Hammers	#	8	10	12	14	16	16	18	20	22
Rotor thickness	mm	14	14	14	14	14	14	14	14	14
Rotor Ø	mm	175	175	175	175	175	175	175	175	175
Rear roller thickness	mm	8	8	8	8	8	8	8	8	8
Rear roller Ø	mm	220	220	220	220	220	220	220	220	220
Main box thickness	mm	8	8	8	8	8	8	8	8	8
Transmission		B 8	B 8	B 8	B 8	B 8	B 8	B 8	B 8	B 8
Recommended power	HP	40	50	50	55	60	65	70	80	90
Weight	Kg	560	590	620	660	680	710	730	760	840



### **SICMA S.R.L.**

LOCALITÀ CALLIPO Z.I. 88022 ACCONIA DI CURINGA (CZ) - ITALY - VAT # IT01805340799

TEL. +39 0968 78240 - WHATSAPP/MOBILE +39 338 8316052

EMAIL: [INFO@SICMASRL.COM](mailto:INFO@SICMASRL.COM) - [INTERNATIONAL@SICMASRL.COM](mailto:INTERNATIONAL@SICMASRL.COM)